

Selective Security Services

Specifications: L2000E Secure Switch

Specifications:

Door: 3/8" steel

Box: 1/4" structural steel

Bolt: 3/8" Tempered Aluminum

Dimensions: outside 4in. X 3in. X 2 3/8in.

box and lid powder coated

Micro switch installed on bolt

Custom lettering on doors available

L2000CE

Cam lock style

The L2000CE is designed to accommodate cam lock cylinders. It requires a custom tailpiece, supplied by Selective Security Services, to deadlock the bolt into the box. Because the lock box is secured using a bolt, it does not rely on the strength of the cam lock's tailpiece to secure the door.

Turning the key activates the micro switch so an entry door or device can be remotely activated.

L2000ME

Mortise lock style

The L2000ME is designed to accommodate 1-1/8" mortise cylinders. The tapered cylinder collar is welded into the door so the lock cylinder can be threaded into the door without the possibility of gripping or twisting the cylinder out of the door with pliers.

The mortise cylinder requires a custom tailpiece, supplied by Selective Security Services, to deadlock the bolt into the box.

Turning the key activates the micro switch so an entry door or device can be remotely activated.



The lock box needs to be anchored to the wall with 5/16" grade 5 (or better) bolts. The lock box is only secure if anchored properly.

