

# Selective Security Services

## Specifications: L3000 Lock Box

### L3000CF

Cam lock style



### Specifications:

Door: 3/8" steel

Box: 1/4" steel

Bolt: 3/8" Tempered Aluminum

Dimensions: outside 4in. X 4in. X 3in.

inside 3.5in. X 3.5in. X 1-5/8in.

box and lid powder coated

Accepts most cam style lock cylinders

Custom lettering on doors available



The L3000CF is designed to accommodate cam lock cylinders. It requires an S-shaped tailpiece to deadlock the bolt into the box. Because the lock box is secured using a bolt, it does not rely on the strength of the cam lock's tailpiece to secure the door.

Cam lock boxes can also be ordered with the hinge option (L3000CFH).



### L3000MF

Mortise lock style



**The lock box needs to be anchored to the wall with 5/16" grade 5 (or better) bolts. The lock box is only secure if anchored properly.**

The L3000MF is designed to accommodate 1-1/8" mortise cylinders. The tapered cylinder collar is welded into the door so the lock cylinder can be threaded into the door without the possibility of gripping or twisting the cylinder out of the door with pliers.

The mortise cylinder requires a #2 tailpiece to deadlock the bolt into the box.

Mortise lock boxes can also be ordered with the hinge option (L3000MFH).

